

# MATERIAL SAFETY DATA SHEET

Emergency Telephone No. (800) 424-9300

**IDENTITY:** SXT Tire -N- Body Cleaner

**CODE:** SXT00500

NFPA Hazard Identification    0 – Least   1 – Slight   2 – Moderate   3 – High   4 – Extreme

Health: 1                                  Fire: 2                                  Reactivity: 0

HMIS CODES:   Health: 1                  Fire: 2                  Reactivity: 0                  Protection: X

---

JB Products LLC

910 Belle Ave Suite 1152

Winter Springs, FL 32708

---

<b>Component Name</b>	<b>CAS Number</b>
-----------------------	-------------------

C10-C13 Isoalkanes	68551-17-7
--------------------	------------

## HAZARDOUS COMBUSTION PRODUCTS

None known

---

**EYE CONTACT:** Contact with eyes may cause irritation

**SKIN CONTACT:** Prolonged or repeated contact may result in skin irritation and dermatitis

**INHALATION:** Vapors may be mildly irritating to lung. Over exposure may result in dizziness, headache, excitation and central nervous system depression

**INGESTION:** Low viscosity material - if swallowed may enter lungs and cause lung damage

---

**EYE CONTACT:** Flush with water for 15 minutes. Get medical attention if irritation persists

**SKIN CONTACT:** Wash skin thoroughly with soap and water. Get medical attention if irritation persists. Soaked clothing should be changed.

**INHALATION:** Remove person from area of exposure. If unconscious, give oxygen. Give artificial respiration if not breathing. Get medical attention.

**INGESTION:** DO NOT INDUCE VOMITING! Danger from aspirating into lungs exceeds short-term toxic effects. Get medical attention.

Advice to Physician: No additional first aid information available.

---

**FLASH POINT (deg F):** 142 (TCC)

**EXTINGUISHING MEDIA:** Use alcohol resistant foam, carbon dioxide or Class BC, ABC fire extinguisher.

**SPECIAL FIRE FIGHTING PROCEDURES:** Self-contained breathing apparatus and protective clothing should be required in fighting fires involving chemicals.

---

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

**Small Spill:** Extinguish possible sources of ignition. Evacuate all unprotected personnel and ventilate area. Only personnel equipped with proper respiratory, skin/eye protection should enter spill area. Dike area to contain spill. Pick up spill or absorbent, non-combustible material. Don't flush into sewers or natural waterways.

**Large Spill:** Contain material as above and call the local fire or police department for immediate emergency assistance.

---

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Keep product away from high energy ignition sources such as heat, sparks, static electricity and open flames. Bond and ground all equipment when transferring from one vessel or container to another. This material can accumulate static charge by flow or agitation. Vapors can ignite by static discharge. Use explosion proof equipment as directed by local fire codes.

**OTHER PRECAUTIONS:** Keep containers tightly closed. Store in cool ventilated area away from heat, sparks or flame.

---

**OSHA Hazardous Component**

**Exposure Limits**

C10-C13 Isoalkanes      OSHA PEL, ppm: None established      ACGIH TLV, ppm: None Established

**RESPIRATORY PROTECTION:** Not usually needed. In confined or enclosed spaces use supplied air respiratory protection

**VENTILATION:** Use in well ventilated area with local exhaust. Equipment must be explosion proof.

**EYE PROTECTION:** Recommended. Safety glasses, goggles or face shield.

**OTHER PROTECTIVE EQUIPMENT:** Protective gloves recommended. Eye fountain and safety shower in work area.

**WORK PRACTICES:** Do not eat, drink or smoke when handling this material

---

Boiling Point (deg F): 325-408      Specific Gravity (H2O=1): .76      Vapor Pressure (mm Hg): 1.5 @ 20 C

Odor: Organic Solvent Odor      Vapor Density (Air=1): >3.0      Solubility in Water: Negligible

Volatile % by Volume: 100      EPA Method 24: 753.8 g/L      pH: Not applicable

Vapor Pressure of VOC Components (mm Hg): 1.0

**APPEARANCE AND ODOR:** Clear liquid, mild hydrocarbon odor

---

**STABILITY:** Stable

**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizers

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS:** Combustion will result in the release of the usual decomposition products including oxides of carbon.

**HAZARDOUS POLYMERIZATION:** Will not occur

---

**WASTE DISPOSAL METHOD:** Product is suitable for burning for fuel value in compliance with applicable laws and regulations and consideration of product characteristics at time of disposal. Conditions of use may cause this material to become a hazardous waste as defined by state or federal law. Use approved treatment, transporters and disposal sites.

**LARGE SPILLS:** Extinguish possible sources of ignition. Evacuate all unprotected personnel and ventilate area. Only personnel equipped with proper respiratory, skin/eye protection should enter spill area. Dike area to contain spill. Pick up spill or absorbent, non-combustible material. Don't flush into sewers or natural waterways.

**EMPTY CONTAINERS:** Keep containers closed when not in use. Do not reuse empty containers. Note flash point is at 142 deg F.

---

**DOT:** <119 gal/container = Not regulated when shipped domestically in non-bulk packaging.  
>119 gal/container = Combustible Liquid - (49CFR 173.120 (b) (2)) Bulk

	<b>US DOT 49CFR172.101</b>	<b>US DOT 49CFR173.120 (b)(2)</b>
<b>PROPER SHIPPING NAME:</b>	Compound, cleaning liquid Non-hazardous, Non-flammable	Hydrocarbons, liquid, n.o.s.
<b>HAZARD CLASS:</b>	None	Combustible Liquid*
<b>UN/NA NUMBER:</b>	None	UN3295
<b>PACKING GROUP:</b>	None	III (Three)
<b>LABEL:</b>	None	Combustible
<b>PLACARD:</b>	None	Combustible/3295
<b>QUANTITY EXEMPTION:</b>	<119 gal/container - Not Regulated	>119 gal/container
<b>OSHA 29 CFR 1910.1200:</b>	C10-C12 Isoalkanes	68551-17-7
<b>States Right to know:</b>	C10-C12 Isoalkanes	68551-17-7MN
<b>TSCA:</b>	Yes	

**CERCLA:** None

**SARA TITLE III, SECTION 313:** None

**CALIFORNIA PROP 65:** None

**SARA TITLE III, SECTION 311/312:** Fire

**SARA TITLE III, SECTION 302:** No

**CANADA WHMIS:** B3

**RoHS COMPLIANT:** Yes

This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we received from sources outside our company and we believe that information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any products in a manner that might infringe existing patents. No warranty is made, either expressed or implied.

---